

CS-G [CS-GL] (For lower rack) PAT.

[CS-G]

*30-degree slope angle(For 2 ~ 5units)
*45-degree slope angle(For 2 ~ 4units)

[CS-GL]

*30-degree slope angle(For 2 ~ 3units)
*45-degree slope angle(For 2 units)

Specifications for Storable Bicycle

Load weight	Tire Diameter	Tire Width	Body Length	Handle Width	Body Height	Stand Pitch	
Less than 40kg ^{*1}	20~28 inch	Less than 55mm	More than 1450mm	Less than 600mm	Less than 1100mm	CS-G: 400mm	CS-GL: 600mm ^{*2}



3 seats bicycle



Electric bicycle

Bicycle with rear basket^{*3}

Infant bicycle



Combo with vertical rack



Combo with top tier



Saving depth

*1 If stored with the double-leg kickstand set

*2 For lower tier

*3 May not be stored continuously

Bicycle Rack that corresponds to electric-assist bicycle with Speed Sensor



CS-G4



CS-GL4

Feature



- Specifications for the speed sensor of a 20-inch electric-assist bicycle that doesn't interfere with bumps. (*Japanese style bicycle)

CS-G

Model	Width (mm)	Depth (mm)	Height (mm)	Qty	Stand Pitch	Unit Price
CS-G3A*	1,198	1,038	686	3	400	¥47,000
CS-G3B*	1,198	1,038	686	3	400	¥47,000
CS-G4	1,598	1,038	686	4	400	¥62,000
CS-G5A*	1,998	1,038	686	5	400	¥77,000
CS-G5B*	1,998	1,038	686	5	400	¥77,000
CS-G6	2,398	1,038	686	6	400	¥91,000

*A starts from lower rack. B starts from higher rack.

CS-GL

Model	Width (mm)	Depth (mm)	Height (mm)	Qty	Stand Pitch	Unit Price
CS-GL3	1,798	542	441	3	600	¥47,000
CS-GL4	2,398	542	441	4	600	¥62,000
CS-GL5	2,998	542	441	5	600	¥77,000
CS-GL6	3,598	542	441	6	600	¥91,000

- Storage may not be possible if bicycles with rear basket continuously stored.
- Storage may not be possible depending on the size and shape of the bicycle.

